



Oxygen Booster C2

Booster for sports use
particularly recommended for divers with CCR,
Thanks to its high performance and reliability and safety
can be used also for larger sizes of cylinders and small groups of divers

a sample of its performance
to fill a three-litre tank starting by a 100-bar storage
less than a minute and a half to go up to 220 bar
even if used for a long time, its unique design makes that the temperature does not increase
This allows the filling is always safe

- Pressure ratio 25/1
- Drive gas pressure 9 - 10 bar
- Piston Stroke 60mm
- High pressure cylinder displacement 20cc
- Maximum boost pressure 340 Bar
- Minimum suction pressure 5 Bar
- Maximum pumping speed 140 cycles/minute
- Minimum pumping speed 15 cycles/minute
- Weight 7 Kg
- Exhaust Oxygen safety



composition materials

Body: Ergal , Stainless Steel 316, Brass OT 58
Seals: Viton ,Ecopur, Teflon, Sintek
Overcooled head and cylinder

The booster is available in two versions

naked as in the picture on top or

in a suitcase full of whips
connections and pressure gauge
pressure reducer to drive the booster

optionally you can have the digital gauge

in this version we have inside the case all we need to recharge our tanks
allows us to carry the suitcase around easily and also hold all of our harvesting

